

"SMART MONITORING OF URBAN INFRASTRUCTURE USING IOT AND PREDICTIVE ANALYTICS"

MOHAMMAD ZAMEER SHEIKH

Principal

SOMAYYA DIPLOMA IN ENGINEERING

cezameer26@gmail.com

AAYUSHI MOHIT BACHIKWAR

Lecturer

Civil Engineering Department

SOMAYYA DIPLOMA IN ENGINEERING

ayushibachikwar@gmail.com

SARVADNY RAHUL NAVALKAR

Student

Civil Engineering Department

SOMAYYA DIPLOMA IN ENGINEERING

tikknavalkar@gmail.com

VAIBHAV VIJAY KOMALWAR

Student

Civil Engineering Department

SOMAYYA DIPLOMA IN ENGINEERING

vaibhavgomalwar43@gmail.com

To Cite this Article

MOHAMMAD ZAMEER SHEIKH, AAYUSHI MOHIT BACHIKWAR, SARVADNY RAHUL NAVALKAR, VAIBHAV VIJAY KOMALWAR, " SMART MONITORING OF URBAN INFRASTRUCTURE USING IOT AND PREDICTIVE ANALYTICS", *Journal of Science Engineering Technology and Management Science*, Vol. 03, Issue 01, January 2026, pp: 109-119, DOI: <http://doi.org/10.64771/jsetms.2026.v03.i01.pp109-119>

Submitted: 25-11-2025

Accepted: 31-12-2025

Published: 13-01-2026

Abstract: Recent urban growth and an aging urban infrastructure have made the safe and efficient management of the roads, bridges, buildings, drainage systems and water distribution networks quite difficult. Traditional inspections mainly rely on field visits and manual observation, but this approach is likely to fail to detect early signs of deterioration. The proposed solution is a smart and adaptive sensing system which integrates IoT sensors with predictive analytics for the continuous monitoring of city infrastructure. The envisioned system consists of a cloud-based monitoring platform and penetrators equipped with a network of distributed sensors to measure strain, vibration, crack width, displacement, temperature, moisture, water level, flow, and pressure. An urban infrastructure dataset was developed using simulation to study the proposed approach in both normal, warning and critical operating conditions. Abnormal behaviour was detected from sensor observations and probability of infrastructure deterioration was estimated by using predictive modelling. The analysis demonstrated that a continuous IoT-based monitoring system would be able to detect abnormal structural service conditions before periodic inspections. The combined time-series and condition-based variables was the most successful analytical approach evaluated, with the best classification performance. The study findings suggest that, when combined with the

benefits of sensing technology, cloud communication and predictive analytics can help to speed up preventive maintenance, enhance infrastructure safety, minimize over- or under-inspections and allow civil engineering authorities to more effectively apply their maintenance resources.

Keywords: IoT; Urban Infrastructure; Predictive Analytics; Structural Monitoring; Smart Maintenance

This is an open access article under the creative commons license
<https://creativecommons.org/licenses/by-nc-nd/4.0/>



Introduction:

The physical fabric of modern cities is provided by urban infrastructure. Roadways, bridges, public life, drainage systems, pipelines, retaining walls, and transportation systems must stay in place and functional throughout their useful lives. These infrastructure systems however are continually subjected to the influences of traffic loading, variations in climate and weather, corrosion, water penetration, ageing of materials, vibration, settlement, extreme environmental conditions etc. If the deterioration is not caught early, it can be a simple problem to become a very expensive repair issue, or a serious safety issue.

Traditional civil infrastructure management method is mainly designating the scheduled inspection model. The periodic inspection of a structure is the responsibility of maintenance teams or engineers, and typically involves documenting visible problems, including cracking, corrosion, settlement, deformation, surface damage, leakage or pavement distresses, that occur during maintenance activities. While this practice is still needed, it does not work as well if the inspections are conducted with a time delay. Any such changes in structure or operations that occur between inspections may thus not be perceived.

As the Internet of Things (IoT) technology has emerged, opportunities have been created for new applications to monitor infrastructure. IoT systems enable the collection and transfer of information continuously by integrating and linking sensors, communication technologies, cloud resources, and analytical tools. Previous researchers on IoT highlighted the need of interconnected sensing devices, with data processing capabilities in cloud infrastructure, while researchers on smart cities showed how urban IoT networks can contribute to the service and management of urban infrastructure (Atzori et al., 2010; Gubbi et al., 2013; Zanella et al., 2014).

In the field of civil engineering, IoT sensors can catalog the various quantities: strain, acceleration, vibration, temperature, humidity, displacement, crack movement, water pressure, flow and environmental exposure. The data collected may not simply be used to report on current status, but also may be used for analysis using predictive approaches. Predictive analytics looks for patterns from past and current data and can provide an indication of whether a monitored component is trending towards an abnormal condition or a critical condition.

Thus, the emergence of IoT and predictive analytics marks a key shift away from reactive maintenance to condition-based and predictive infrastructure management. Instead of waiting for the observed deterioration or failure, patterns of unusual occurrences can be detected, priorities can be set for inspections and maintenance can be done in advance of significant

deterioration or failure. The aim of the present study is to design and test a smart monitoring concept towards various types of urban civil infrastructure.

Related Works:

Early research in structural health monitoring demonstrated the importance of sensor-based observation for evaluating changes in civil structures. Spencer, Ruiz-Sandoval, and Kurata (2004) discussed the potential of smart sensors containing processing and wireless communication capabilities for monitoring infrastructure. Their work highlighted both the opportunities and technical difficulties associated with large distributed sensor networks.

Lynch and Loh (2006) reviewed wireless sensors and wireless sensor networks for structural health monitoring. They observed that wireless sensing could reduce the dependence on extensive cabling while also allowing local processing of structural response information. This development was important for large structures where traditional wired monitoring networks may be expensive or difficult to install.

Farrar and Worden (2007) presented structural health monitoring as a systematic process for identifying changes that may influence structural performance. Their work strengthened the connection between sensing, damage identification, and data analysis within engineering monitoring systems.

With the growth of IoT, sensing systems became increasingly connected to cloud platforms and urban communication networks. Atzori et al. (2010) described IoT as an integration of sensing, identification, communication, and intelligent processing technologies. Gubbi et al. (2013) further discussed cloud-oriented IoT architecture and the use of distributed sensing for environmental and urban applications. Zanella et al. (2014) specifically examined IoT architecture for smart cities and demonstrated the role of interconnected devices in urban services.

More recent civil engineering studies have concentrated on combining sensor measurements with intelligent analytical methods. Avci et al. (2021) reviewed machine-learning and deep-learning methods for vibration-based damage detection in civil structures and showed the growing relevance of data-driven methods in structural condition assessment.

Mishra, Lourenço, and Ramana (2022) reviewed IoT-based structural health monitoring and identified applications including crack detection, vibration monitoring, concrete performance assessment, corrosion diagnosis, road-condition monitoring, and seismic vulnerability assessment. Their study emphasized the ability of IoT systems to provide real-time civil infrastructure information through cloud-based platforms.

Recent work has also connected civil infrastructure monitoring with digital-twin and predictive-management concepts. Reviews of digital twins for civil infrastructure show that continuously updated physical and digital information can support infrastructure assessment, maintenance, and future performance evaluation.

Bhatta and Dang (2024) further reviewed IoT-based structural health monitoring for buildings, bridges, and other civil structures, highlighting the increasing importance of real-time monitoring while also identifying issues related to communication reliability, sensor durability, data management, and implementation cost.

The existing literature demonstrates considerable progress in sensing and structural health monitoring. However, there remains a need for integrated frameworks in which different categories of urban infrastructure can be monitored within a common system and the

collected information can be converted into predictive maintenance decisions. The present study addresses this requirement by combining IoT sensing, condition classification, and predictive analytics within a unified civil infrastructure monitoring framework.

Objectives of the Study:

1. To develop an IoT-based framework for continuous monitoring of structural, environmental, and operational parameters of urban civil infrastructure.
2. To apply predictive analytics for early identification of abnormal conditions and estimation of infrastructure deterioration.
3. To evaluate the potential of smart monitoring for improving maintenance planning, inspection efficiency, and urban infrastructure safety.

Material and Methods:

The study adopted a simulation-based quantitative methodology for evaluating an integrated smart infrastructure monitoring system. The proposed framework represents a typical urban monitoring environment containing bridges, roads, municipal buildings, drainage points, and water-distribution components.

Monitoring Framework:

The monitoring system was divided into four main layers:

Sensing Layer:

IoT sensors were assigned to infrastructure components according to the physical parameter being monitored.

Communication Layer:

Sensor observations were transferred through Wi-Fi, Lora WAN, cellular communication, or gateway devices.

Data and Cloud Layer:

Incoming information was stored in a centralized database. Time stamps and infrastructure identification numbers were attached to each observation.

Analytics and Decision Layer:

The collected information was processed using threshold analysis, trend analysis, anomaly detection, and predictive classification. Alerts were categorized as Normal, Warning, or Critical.

Table 1. Proposed IoT Monitoring Arrangement

Infrastructure Component	IoT Sensor	Parameter Monitored	Civil Engineering Purpose
Bridge	Strain gauge	Structural strain	Identification of unusual stress behaviour
Bridge	Accelerometer	Vibration	Monitoring dynamic response
Building	Crack sensor	Crack width	Detection of crack propagation
Building	Tilt sensor	Inclination	Identification of abnormal movement
Road	Vibration/condition sensor	Surface response	Detection of pavement deterioration

Drainage system	Water-level sensor	Water depth	Flood and blockage monitoring
Water pipeline	Pressure sensor	Pressure	Leakage or pressure-loss detection
Water network	Flow sensor	Discharge	Identification of abnormal flow
All assets	Temperature sensor	Temperature	Environmental correction
All assets	Humidity/moisture sensor	Moisture	Exposure and durability assessment

Dataset Development

Since an actual municipal monitoring database was not supplied for the study, a simulated dataset representing **90 days of monitoring** was prepared. The model contained four infrastructure groups:

- 4 bridge monitoring locations,
- 4 road segments,
- 3 public building locations,
- 4 drainage and water-network locations.

Sensor observations were generated at regular time intervals under three infrastructure-condition categories: Normal, Warning, and Critical.

A total of **18,000 monitoring records** were considered after data cleaning. Each record contained the asset identification, monitoring time, sensor value, environmental condition, previous sensor trend, and infrastructure-condition category.

Data pre-processing:

The following operations were carried out before analysis:

- removal of duplicate observations;
- identification of missing values;
- smoothing of isolated sensor noise;
- normalization of numerical parameters;
- calculation of moving averages;
- calculation of rate of change;
- classification of threshold exceedance;
- separation of training and testing datasets.

Seventy percent of the observations were used for model training and 30% were retained for testing.

Predictive Analytical Models:

Three predictive approaches were examined:

Random Forest: used for classifying infrastructure condition from multiple sensor parameters.

Gradient Boosting: used to improve classification of complex relationships between environmental and structural variables.

Long Short-Term Memory (LSTM): used for analysing temporal behaviour where present infrastructure condition depends on previous sensor observations.

Model performance was evaluated using accuracy, precision, recall, and F1-score.

The standard measures were calculated as:

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$

$$Precision = \frac{TP}{TP + FP}$$

$$Recall = \frac{TP}{TP + FN}$$

and

$$F1 = 2 \times \frac{Precision \times Recall}{Precision + Recall}$$

where TP represents true positives, TN represents true negatives, FP represents false positives, and FN represents false negatives.

Condition Classification

To convert sensor observations into engineering information, three general condition levels were adopted.

Table 2. Infrastructure Condition Classification

Condition	General Sensor Behaviour	Engineering Interpretation	Recommended Action
Normal	Stable and within expected range	Infrastructure operating normally	Routine monitoring
Warning	Gradual increase or moderate threshold exceedance	Possible deterioration developing	Detailed inspection
Critical	Rapid change or major threshold exceedance	High probability of serious defect	Immediate engineering assessment

The thresholds in an actual field implementation should be determined separately for every structure using design requirements, material properties, baseline observations, relevant standards, and engineering judgement.

Analysis of the Study:

The analysis was done in three phases. First, the distribution of the conditions of infrastructure was found. Second, abnormal behaviour was detected by analysing the trends of the sensors. Third, the predictive models were compared to check their classification performance in infrastructure condition.

The 18,000 monitoring simulations indicated that the majority (72%) were of normal operating behaviour, about 20% were related to warning behaviour, and 8% of the simulations were related to critical behaviour. This distribution represents a monitoring system where the majority of infrastructure can be operated, and smaller number of infrastructure needs engineering attention.

Table 3. Distribution of Monitoring Observations

Infrastructure Condition	Number of Records	Percentage
Normal	12,960	72%
Warning	3,600	20%

Critical	1,440	8%
Total	18,000	100%

The individual trends produced by the sensor analysis revealed that use of combinations of variables is more informative than use of individual variables. An isolated case of bridge vibration could be due to travel load using a temporary structure. But with an increasing vibration coupled with abnormal strain and a trend of vibration increases over time is better evidence that engineering inspection might be needed.

The same applies to buildings, high levels of moisture alone are not a sign of structural damage. If together with the increase in the crack width/displacement, high moisture exists, then together the observation parameters are helpful to have information for the condition.

Water-level data was most useful as a time series for drainage infrastructure. Rapid increase can be followed by unusually slow decrease - consider partial blockage or inadequate discharge capacity. The criteria in the pipeline monitoring were the pressure drop and abnormal flow, combinations of which were considered as possible leakage signatures.

Predictive Model Performance

The three models were evaluated using the testing portion of the simulated monitoring database.

Table 4. Performance of Predictive Models

Predictive Model	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)
Random Forest	91.8	90.6	89.7	90.1
Gradient Boosting	93.6	92.5	91.9	92.2
LSTM	95.1	94.3	93.7	94.0

The LSTM-based approach achieved the highest simulated classification accuracy of **95.1%**. Its stronger performance can be associated with its ability to consider sequences of observations instead of analysing measurements independently. This characteristic is relevant to civil infrastructure because deterioration normally develops progressively over time.

Gradient Boosting also achieved strong performance, with an accuracy of 93.6%, while Random Forest obtained 91.8%. The results indicate that conventional machine-learning models can still provide useful infrastructure-condition classification where computational resources or historical datasets are limited.

Comparison with Conventional Monitoring

The potential operational differences between conventional inspection and the proposed smart monitoring approach were also examined.

Table 5. Conventional and Smart Infrastructure Monitoring

Monitoring Factor	Conventional Approach	IoT-Predictive Approach
Data collection	Periodic	Continuous or near real time
Inspection dependency	High	Moderate
Early abnormality detection	Limited	High
Remote monitoring	Limited	Available
Historical trend analysis	Often manual	Automated
Maintenance approach	Reactive/periodic	Condition-based/predictive

Warning generation	After inspection	Automated
Data volume	Low to moderate	High
Initial technology cost	Lower	Higher
Long-term monitoring capability	Moderate	High


The comparison suggests that IoT monitoring should not be considered a complete replacement for professional civil engineering inspection.

Results and Discussion:

The study shows it is possible to get a more current insight on the condition of the infrastructure by integrating the use of sensors. The study illustrates how IoT sensors can, when combined with predictive analytics, allow for a more up-to-date view on infrastructure condition than periodic inspection. Structural and environmental variables can be continuously measured to allow observation of changes over time in addition to conditions observed on a building inspection.

A key finding is that using a combination of sensor parameters may prove valuable. The deterioration of infrastructure can hardly be measured with just one parameter. Operating conditions, occupancy, rainfall, humidity, temperature, wind and traffic can influence the structural response of a building. Thus, measuring more sensor parameters together gives more confidence in representing the health of the infrastructure.

Finally, through simulated analytical results, it illustrates the value of information depending upon time. The best classification results were achieved by the LSTM method due to the fact that deterioration in infrastructure frequently has a continuous aspect to it. It may be more important that the strain and displacement are increasing gradually over time and the crack width, water level or pressure variation are increasing separately.



These results align with the common trend of using machine-learning methods to identify anomalous trends in structure health monitoring data. The approach of using machine-learning and deep-learning (ML/DL) techniques has been increasingly studied for vibration-based structural damage assessment and other civil engineering projects.

The system from a maintenance point of view could help infrastructure managers prioritise scarce resources. A large number of urban assets might be subjected to inspection based on a scheduled timetable, and significant amounts of time could be devoted to reviewing those assets that are in satisfactory condition. An intelligent surveillance system would be able to detect and assign higher priority of supervision on assets showing abnormal behavior.

In extreme environmental events the system can also be beneficial. Changes in infrastructure response can occur very quickly during periods of heavy rainfall, flooding events, earthquakes, or periods of unusually high levels of traffic loading and/or extreme temperatures. The continuous monitoring enables an engineer to study such changes from a distance and decide whether to go on location.

Some challenges have been presented, however, when using IoT for monitoring. Sensors are mounted on infrastructure structures, and come with the challenges of moisture, dust, temperature fluctuations, vibration, vandalism and power constraints. The interruption of signals or network failures can also affect wireless communication. For large sensor networks, collecting a lot of data will result in the need for secure data storage, processing reliability, calibration and cyber-security.

The other factor to consider is false alarm control. It should not assume that all of the short-term fluctuations are infrastructures damage. The engineering knowledge and baseline monitoring, along with the structural design information and field validation are therefore needed to establish threshold limits.

Average costs are a limit, too. Initial investment for installing sensors, communication gateways, cloud services, data-management platforms and maintenance systems. However, the potential benefit over the long-term may be worth a lot if failures are avoided surreptitiously, unnecessary inspections are avoided, or a failure can be stopped in time before a situation grows too serious.

It needs to be noted that the present numerical results are for a set of data from a simulation context and, thus, should be interpreted as an illustration of the proposed methodology and not as a result of a direct measurement at an actual municipality. Next steps in the field will involve placement of IoT sensors on existing bridges, roads, buildings, etc., drainage systems, or pipelines and their expected predictions for a period of sufficient duration for the inspection to take place.

Conclusion:

The paper proposes a holistic approach to smart monitoring of civil infrastructures in cities using the synergistic use of IoT based sensors and predictive analytics. The framework can be used to gather structural, environmental and operational data on an ongoing basis and be converted to condition-based engineering information.

The simulation-based analysis showed that the information collected by the sensors can be segmented into "normal", "warning", and "critical" conditions, and applied for predictive maintenance of infrastructure. From all the analytical methods analysed, LSTM model gave the best simulated classification accuracy followed by Gradient Boosting and Random Forest.

The results also indicated that the use of several parameters and study on their behaviour through time can have more meaningful information, as compared to using the individual sensor parameters.

Its ability to monitor the condition of an infrastructure through IOT can help identify issues early, do condition assessments remotely, optimize inspection frequency and schedule maintenance more effectively. It's especially well-suited for areas that are urban in nature and have a lot of bridges, roads, buildings, drainage, and utility networks that have to be managed at once.

These benefits notwithstanding, usage of smart monitoring systems should be an additional choice rather than a replacement to professional civil engineering inspection. What is necessary for successful implementation are reliable sensors, the correct threshold values, cyber security, communication stability, regular calibration, and engineering interpretation. Some challenges for future research are that: long-term field validation, integration with Building Information Modelling and digital twins, producing long-term predictive models for each asset, and creating city-scale monitoring dashboards. These developments can play a role in safer, resilient and efficient urban infrastructure.

References:

1. Atzori, L., Iera, A., & Morabito, G. (2010). The Internet of Things: A survey. *Computer Networks*, 54(15), 2787–2805. <https://doi.org/10.1016/j.comnet.2010.05.010>.
2. Avci, O., Abdeljaber, O., Kiranyaz, S., Hussein, M., Gabbouj, M., & Inman, D. J. (2021). A review of vibration-based damage detection in civil structures: From traditional methods to machine learning and deep learning applications. *Mechanical Systems and Signal Processing*, 147, 107077. <https://doi.org/10.1016/j.ymssp.2020.107077>.
3. Bhatta, S., & Dang, J. (2024). Use of IoT for structural health monitoring of civil engineering structures: A state-of-the-art review. *Urban Lifeline*, 2, 17. <https://doi.org/10.1007/s44285-024-00031-2>.
4. Farrar, C. R., & Worden, K. (2007). An introduction to structural health monitoring. *Philosophical Transactions of the Royal Society A*, 365(1851), 303–315. <https://doi.org/10.1098/rsta.2006.1928>.
5. Gubbi, J., Buyya, R., Marusic, S., & Palaniswami, M. (2013). Internet of Things (IoT): A vision, architectural elements, and future directions. *Future Generation Computer Systems*, 29(7), 1645–1660. <https://doi.org/10.1016/j.future.2013.01.010>.
6. Liu, C., Zhang, P., & Xu, X. (2023). Literature review of digital twin technologies for civil infrastructure. *Journal of Infrastructure Intelligence and Resilience*, 2(3), 100050. <https://doi.org/10.1016/j.iintel.2023.100050>.
7. Lynch, J. P., & Loh, K. J. (2006). A summary review of wireless sensors and sensor networks for structural health monitoring. *The Shock and Vibration Digest*, 38(2), 91–128. <https://doi.org/10.1177/0583102406061499>.
8. Mishra, M., Lourenço, P. B., & Ramana, G. V. (2022). Structural health monitoring of civil engineering structures by using the Internet of Things: A review. *Journal of Building Engineering*, 48, 103954. <https://doi.org/10.1016/j.jobbe.2021.103954>.

9. Naderi, H., & Shojaei, A. (2023). Digital twinning of civil infrastructures: Current state of model architectures, interoperability solutions, and future prospects. *Automation in Construction*, 149, 104785. <https://doi.org/10.1016/j.autcon.2023.104785>.
10. Spencer, B. F., Ruiz-Sandoval, M. E., & Kurata, N. (2004). Smart sensing technology: Opportunities and challenges. *Structural Control and Health Monitoring*, 11(4), 349–368. <https://doi.org/10.1002/stc.48>.
11. Zanella, A., Bui, N., Castellani, A., Vangelista, L., & Zorzi, M. (2014). Internet of Things for smart cities. *IEEE Internet of Things Journal*, 1(1), 22–32. <https://doi.org/10.1109/JIOT.2014.2306328>.